

210 kg/ 24h

Granular ice makers / Granular ice makers:
B95C - B130C - B160C - B200C - B125 - B165 - B205 - B305S - B405 - B505

B200C ALLGAS
220-240/50/1
Granular ice makers



USB



PROGRAMMED
OZONE CYCLE



SCHEDULED
PRODUCTION



TOUCH
CONTROL



BLUETOOTH

FEATURES

- Steel shell
- Air and water condensation
- Sanitization cycle
- Capacitive control key
- Audible and light signaling alarms
- HACCP Alarm Report
- USB connection for sw update and HACCP data download
- Condenser fan controlled at low ambient temperatures
- Programmable ice production
- Predictive failure analysis
- Equipment performance report
- Removable and washable air filter
- Frontal air intake and exhaust



OPTIONAL

- Programmable sanitizing cycle with ozone
- IOT cloud connection

RECOMMENDED DEPOSITS

50 kg

DIMENSIONS

L x P x H (mm)



700 x 650 x 995



760 x 720 x 1070

VOLTAGE



220-240/50/1
220/60/1

GAS



R290
GWP 3

TECHNICAL DATA



cond



comp. W



ABS. W



Fuse



Kwh/100Kg



l / h



Kg



Kg

B200C AG 220-240/50/1N



878

720

10

10.2

6.5

65

72

B200C AG 220-240/50/1N



878

600

10

8

53

65

72

ICE TYPE

RESIDUAL WATER
CONTENUTO
ACQUA



Flake Ice

25%

ICE PRODUCTION

kg/24h
lbs/24h

Air cooling



Temp. Aria Air Temp.	Temp. Acqua /Water Temp.			
°C / °F	10° 50°	15° 59°	21° 70°	32° 90°
10° 50°	210 463	198 436	194 428	180 397
21° 70°	190 419	181 399	174 383	160 353
32° 90°	169 372	162 357	155 342	140 309
38° 100°	160 353	154 339	147 324	133 293

Water cooling



Temp. Aria Air Temp.	Temp. Acqua /Water Temp.			
°C / °F	10° 50°	15° 59°	21° 70°	32° 90°
10° 50°	195 430	185 408	179 395	162 357
21° 70°	191 421	181 399	175 386	160 353
32° 90°	182 401	175 386	168 370	154 339
38° 100°	167 368	161 355	154 339	140 309

210 kg/ 24h

Granular ice makers / Granular ice makers:


B95C - B130C - B160C - B200C - B125 - B165 - B205 - B305S - B405 - B505

B200C ALLGAS

220-240/50/1


Granular ice makers

DIMENSIONS



MyICE


Allows control and monitoring of ice makers directly from smartphones / Allows control and monitoring of ice makers directly from smartphones



Operating conditions

	Min	Max
Temp. Ambient	10°C	40°C
Temp. Water Ice	5°	35°
Water Pressure	1 Bar (14psi)	10 Bar (140psi)
Conductivity water	20 microS	500 microS
Power Supply	-10%	+10%

TOUCH CONTROL



Capacitive Stand-by / Start button
(LED continuously changing colors from white to red)

Heat expelled	2905 W
Air Volume	300 m³/h